

2008



Hoosier[®]

RACING TIRE

Drag Product Information

www.hoosiertire.com

Prices subject to change without notice.

DRAG RACING

ITEM NUMBER	TIRE SIZE	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM RIM	MEASURED RIM	SECTION WIDTH	TIRE COMPOUNDS	RACERS WEIGHT	NET
Drag Front										
18085	23.0/ 5.0-15	4.8"	23.0"	72.0"	3.5-4"	3.5"	5.8"	Drag Front	10	139.00
18095	24.0/ 5.0-15	4.8"	23.8"	75.0"	3.5-4"	3.5"	5.8"	Drag Front	11	140.00
18102	25.0/ 5.0-15	4.8"	24.8"	77.9"	3.5-4"	3.5"	5.8"	Drag Front	11	143.00
18105	26.0/ 4.5-15	4.3"	25.8"	81.0"	3.5-4"	3.5"	5.9"	Drag Front	11	145.00
18107	28.0/ 4.5-15	4.5"	27.7"	87.0"	3.5-4"	4"	7.6"	Drag Front	12	147.00
18108	22.0/ 2.5-17	1.5"	22.0"	69.0"	2.5"	2.5"	2.7"	Dragster Front	4	135.00
Drive Tires - Slicks										
18110	26.0/ 8.0-15	8.0"	26.1"	82.0"	7-8"	8"	9.7"	D06	17	165.00
18120	26.0/ 9.0-15	9.0"	26.1"	82.0"	7-8"	8"	10.3"	D06	18	166.00
18130	26.0/10.0-15	10.0"	26.4"	83.0"	8-10"	9"	11.5"	D06	20	171.00
18140	28.0/ 9.0-15	9.0"	28.0"	88.0"	8-10"	8"	11.1"	D06	21	168.00
18150	28.0/10.0-15	10.0"	28.0"	88.0"	8-10"	8"	11.7"	D06	22	173.00
18153	28.0/10.0-16	10.0"	28.0"	88.0"	8-10"	10"	12.0"	C07	23	183.00
18154	10.5/28.0-15	10.0"	28.0"	88.0"	8-10"	8"	12.6"	C07	26	178.00
18155	28.0/10.5-15	10.2"	28.0"	88.0"	8-10"	8"	12.0"	C07	24	183.00
18160	29.0/ 9.0-15	9.0"	29.1"	91.5"	8-10"	8"	11.4"	D06	22	176.00
18170	29.0/10.0-15	10.0"	29.1"	91.5"	8-10"	8"	11.9"	D06	24	181.00
18175	29.0/10.5-15 W*	11.0"	29.3"	92.0"	8-10"	10"	13.2"	D06	25	198.00
18180	29.0/11.0-15	11.0"	29.3"	92.0"	8-10"	10"	13.2"D06		25	193.00
18190	29.0/12.0-15	12.0"	29.3"	92.0"	10-12"	10"	13.7"	D06	26	198.00
18192	29.5/10.5-15	11.1"	30.6"	96.0"	10-12"	10"	13.2"	D06	26	194.00
18193	29.5/10.5-15	10.5"	30.0"	94.0"	10-12"	10"	13.1"	C11	28	196.00
18195	29.5/11.5-15 W*	13.5"	30.6"	96.0"	12-14"	12"	15.2"	D06	30	203.00
18200	30.0/ 9.0-15	9.0"	30.0"	94.0"	8-10"	8"	11.8"	D05, D07	22	198.00
18205	30.0/10.5-15	10.5"	30.0"	94.0"	8-10"	10"	13.1"	D05	22	210.00
18209	30.0/9.0R-15 Radial***	9.0"	29.5"	92.5"	8-10"	8"	11.3"	C06	22	218.00
18210	30.0/9.0R-15 Radial	9.0"	29.5"	92.5"	8-10"	8"	11.3"	C07	24	218.00
18211	9.0/30.0R-15 Radial	9.0"	29.9"	94.0"	8-10"	8"	11.3"	C07	24	219.00
18212	9.0/30.0R-15 Radial***	9.0"	29.9"	94.0"	8-10"	8"	11.3"	C06	22	219.00
18214	30.0/10.5R-15 Radial***	10.5"	29.5"	92.5"	9-10"	10"	12.5"	C06	23	231.00
18215	30.0/10.5R-15 Radial	10.5"	29.5"	92.5"	9-10"	10"	12.5"	C07	26	231.00
18221	31.0/10.5-15	11.0"	30.8"	97.0"	10-12"	12"	14.7"	C07	30	234.00
18235	31.5/12.5-15W*	13.5"	31.7"	99.5"	12-14"	14"	17.2"	D05	33	250.00
18237	13.5/31.5-15L***	13.5"	31.7"	99.5"	12-14"	14"	17.2"	C07	28	249.00
18239	31.5/13.5R-15	13.5"	31.8"	99.7"	12-14"	14"	16.9"	C06	28	289.00
18240	31.0/14.0-15	14.0"	31.2"	98.0"	12-14"	12"	16.5"	D05	33	256.00
18242	32.0/12.0-15	12.2"	32.0"	101.0"	10-12"	12"	15.8"	D05	28	257.00
18243	32.0/13.0-15	13.2"	32.0"	101.0"	12-13"	12"	16.5"	D05	29	259.00
18245	32.0/13.5-15 W*	14.0"	32.3"	102.0"	12-14"	14"	17.7"	D05	35	268.00
18247	32.0/13.5R-15 Radial	13.5"	32.2"	101.2"	14-15"	14"	17.0"	C06	31	298.00
18250	32.0/14.0-15	14.0"	32.3"	102.0"	12-14"	14"	17.7"	D05	34	268.00
18255	14.0/32.0-15 L***	14.0"	32.3"	102.0"	12-14"	14"	17.8"	C07	31	268.00
18260	32.0/14.5-15 W*	15.0"	32.6"	102.5"	14-15"	14"	18.4"	D05	37	271.00
18265	14.5/32.0-15 L***	15.0"	32.3"	102.0"	14-15"	14"	18.4"	C07	32	271.00
18267	32.0/14.5R-15 Radial	15.0"	32.2"	101.2"	14-16"	14"	18.1"	C06	31	304.00
18280	32.0/17.0-15	17.2"	32.3"	102.0"	15-16"	16"	20.7"	D06	40	290.00
18300	32.5/16.5-15	16.7"	32.3"	101.5"	15-16"	15"	19.8"	C07	38	287.00
18331	33.0/10.5-15	10.9"	33.0"	104.0"	10-12"	12"	15.6"	C11	33	243.00
18335	10.5/33.0-16	11.5"	33.4"	105.0"	14-16"	15"	17.3"	C11	33	257.00
18350	33.0/12.0-15	12.2"	33.0"	102.0"	10-12"	10"	15.2"	C09	28	264.00
18361	33.0/14.5R-15 Radial	15.0"	33.0"	104.0"	14-16"	14"	18.4"	C06	35	311.00
18367	14.5/33.0-15 L***	14.5"	33.0"	104.0"	14-15"	14"	18.2"	C07	33	274.00
18370	33.0/15.0-15	15.0"	33.0"	104.0"	14-15"	14"	18.7"	D05	36	278.00
18400	33.0/16.0-15	17.0"	33.0"	104.0"	15-16"	15"	19.8"	D05, D06, C07	38	292.00
18450	33.0/16.5-15 S**	17.0"	33.0"	104.0"	15-16"	15"	19.8"	D06, C07	38	292.00
18500	33.0/17.0-16	17.0"	33.0"	104.0"	15-16"	15"	19.8"	C07	39	306.00
18600	33.5/16.0-15	17.0"	33.6"	106.0"	15-16"	15"	19.8"	C07	39	315.00
18640	33.5/16.5-16 S**	17.0"	33.6"	106.0"	15-16"	16"	19.9"	C07	39	315.00
18650	33.5/17.0-16	17.0"	33.6"	106.0"	15-16"	16"	19.9"	C07	39	315.00
18700	33.5/17.0-16	17.0"	33.6"	106.0"	15-16"	16"	20.7"	C06	40	345.00
18750	33.5/17.0-16	17.0"	33.5"	105.0"	15-16"	16"	19.9"	PSI	41	427.00
18790	34.5/17.0-16	17.0"	35.0"	110.0"	15-16"	16"	21.4"	C2055	42	384.00
18800	34.5/17.0-16	17.0"	35.0"	110.0"	15-16"	16"	21.4"	C4000	42	384.00
18900	36.0/17.0-16	17.0"	36.2"	114.0"	15-16"	16"	21.7"	C2055	44	427.00



D.O.T. DRAG RADIALS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS	TIRE WEIGHT	RACERS NET
17310	P225/50R-15	M	8.5"	24.2"	70.0"	7-9"	7"	9.3"	DRAG RADIAL	18	176.00
17315	P275/50R-15	M	9.5"	25.7"	80.5"	8-10"	9"	10.8"	DRAG RADIAL	22	180.00
17316	P295/65R-15	M	10.0"	29.5"	93.5"	8-10"	9"	12.0"	DRAG RADIAL	27	187.00
17317	P275/60R-15	M	10.0"	28.0"	88.0"	8-10"	8"	11.5"	DRAG RADIAL	24	186.00
17318	P325/50R-15	M	11.75"	28.0"	88.0"	9-11"	10"	13.0"	DRAG RADIAL	29	188.00
17319	P315/60R-15	M	11.0"	29.7"	93.5"	9-11"	10"	13.5"	DRAG RADIAL	30	188.00
17320	P225/50R-16	M	8.5"	24.9"	78.3"	7-9"	7"	9.5"	DRAG RADIAL	18	186.00
17325	P255/50R-16	M	9.25"	26.4"	83.0"	8-10"	8"	10.5"	DRAG RADIAL	22	191.00
17330	P275/40R-17	M	9.8"	25.7"	81.0"	9-11"	10"	11.3"	DRAG RADIAL	21	196.00
17332	P315/35R-17	M	11.1"	25.6"	81.6"	9-11"	11"	12.6"	DRAG RADIAL	26	198.00
17335	P335/35R-17	M	12.5"	25.4"	82.0"	11-13"	12"	13.5"	DRAG RADIAL	27	201.00

QUICK TIME D.O.T.

ITEM NUMBER	TIRE SIZE	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS	TIRE WEIGHT	RACERS NET
17010	P175/70D-15	5.6"	24.8"	78.0"	5-6"	5"	7.3"	Quick Time Frt	15	140.00
17030	P275/55D-14	8.5"	26.1"	82.0"	6-8"	8"	10.1"	Quick Time	19	165.00
17050	P245/60D-15	8.0"	26.1"	82.0"	6-8"	8"	11.1"	Quick Time	17	165.00
17110	P275/60D-15	9.0"	27.0"	85.0"	8-10"	8"	11.8"	Quick Time	19	167.00
17100	P275/50D-15	10.0"	26.1"	82.0"	8-10"	8"	11.6"	Quick Time	21	172.00
17125	P295/60D-15	10.0"	29.0"	92.0"	8-10"	8"	12.6"	Quick Time	20	179.00
17120	P295/50D-15	10.0"	27.0"	85.0"	8-10"	8"	12.8"	Quick Time	22	176.00
17130	P325/50D-15	10.5"	27.8"	87.5"	8-10"	8"	13.1"	Quick Time	23	186.00
17140	31 X 16.50-15LT	14.0"	30.9"	97.0"	12-14"	14"	17.8"	Quick Time	30	243.00
17150	31 X 18.50-15LT	15.0"	30.9"	97.0"	14-15"	14"	18.3"	Quick Time	33	254.00
17210	33 X 22.50-15LT	17.0"	33.0"	103.5"	15-16"	15"	21.1"	Quick Time	39	329.00

QUICK TIME PRO D.O.T.

ITEM NUMBER	TIRE SIZE	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS	TIRE WEIGHT	RACERS NET
17410	26 X 9.50-14LT	8.0"	26.1"	82.0"	6-8"	8"	9.3"	Quick Time Pro	17	171.00
17400	26 X 9.50-15LT	8.0"	26.1"	82.0"	6-8"	8"	9.5"	Quick Time Pro	17	171.00
17430	26 X 9.50-16LT	8.0"	26.1"	82.0"	6-8"	8"	9.3"	Quick Time Pro	18	183.00
17420	26 X 11.50-15LT	10.0"	26.4"	83.0"	8-10"	8"	10.8"	Quick Time Pro	20	179.00
17500	27 X 10.50-15LT	9.0"	27.0"	85.0"	8-10"	8"	10.1"	Quick Time Pro	19	178.00
17510	27 X 11.50-15LT	10.0"	27.0"	85.0"	8-10"	8"	11.2"	Quick Time Pro	22	181.00
17601	28 X 11.50-15LT	10.0"	28.0"	88.0"	8-10"	8"	11.2"	Quick Time Pro	20	186.00
17603	28 X 11.50-16LT	10.0"	28.0"	88.0"	8-10"	10"	11.8"	Quick Time Pro	24	191.00
17606	28 X 13.50-15LT	11.0"	28.0"	88.0"	10-12"	10"	12.9"	Quick Time Pro	22	193.00
17611	28 X 14.50-15LT	12.0"	28.0"	88.0"	10-12"	10"	13.1"	Quick Time Pro	25	195.00
17651	28 X 14.50-16LT	12.0"	28.0"	88.0"	10-12"	10"	12.9"	Quick Time Pro	27	198.00
17700	29 X 11.50-15LT	10.0"	29.3"	92.0"	8-10"	8"	11.9"	Quick Time Pro	24	193.00
17705	29 X 13.50-15LT	11.0"	29.3"	92.0"	10-12"	10"	13.4"	Quick Time Pro	25	195.00
17710	29 X 14.50-15LT	12.0"	29.3"	92.0"	10-12"	10"	13.9"	Quick Time Pro	26	197.00
17790	31 X 13.50-15LT	11.0"	30.9"	97.0"	10-12"	10"	14.1"	Quick Time Pro	29	226.00
17800	31 X 16.50-15LT	13.0"	30.9"	97.0"	12-14"	12"	16.0"	Quick Time Pro	32	247.00
17810	31 X 18.50-15LT	15.0"	30.9"	97.0"	14-15"	14"	17.9"	Quick Time Pro	34	264.00
17900	33 X 18.50-15LT	15.0"	33.0"	104.0"	14-15"	14"	18.5"	Quick Time Pro	38	303.00
17910	33 X 22.50-15LT	17.0"	33.0"	104.0"	15-16"	15"	20.0"	Quick Time Pro	39	326.00
17950	35 X 22.50-16LT	17.0"	35.0"	110.0"	15-16"	16"	21.5"	Quick Time Pro	46	370.00

NOTE: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

RACING TUBES & LINER

ITEM NUMBER	TUBE SIZE			RACERS NET
288088-15	80/ 88-15 TUBE	WILL FIT 80" TO 88" CIRC.	6" TO 11" TREAD WIDTH	59.04
2886100-15	86/100-15 TUBE	WILL FIT 86" TO 100" CIRC.	11" TO 13" TREAD WIDTH	62.38
2894106-15	94/106-15 TUBE	WILL FIT 94" TO 106" CIRC.	15" TO 19" TREAD WIDTH	71.29
32400	75/16.0-16 LINER	FOR USE IN CATALOG # 18790, # 18800, # 18900		128.75

JR DRAGSTER

ITEM NUMBER	TIRE SIZE	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS	TIRE WEIGHT	RACERS NET
18030	18.0/ 8.0-8	7.7"	17.7"	55.5"	7-8"	8"	9.9"	JR1	4.4	103.00
18040	18.0/ 10.0-8	9.5	17.7"	55.5"	8-10"	8"	10.6"	JR1	5.0	108.00

NO WARRANTY POLICY

Hoosier Racing Tire Corp. offers racing tires for sale only upon the conditions and the terms contained in this disclaimer of liability and indemnity. Due to many varied and different conditions which Hoosier Racing Tires and Tubes are exposed and because of the manner in which racing is conducted, Hoosier Racing Tire Corp. makes absolutely **no warranty**, expressed or implied, as to the fitness for a general or particular purpose or of merchantability in connection with any offer of sale of Hoosier Racing Tires and tubes. **"HOOSIER RACING TIRES AND TUBES ARE SOLD AS IS."** Race tires are not tested or labeled to meet FMVSS 109 or ECE 36 Safety Standards. Therefore it is dangerous and illegal to sell race tires for use on public highways. Any person selling Hoosier Racing Tires or Tubes for highway use agrees to indemnify and reimburse Hoosier Racing Tire Corp. for all loss, damage, or liability Hoosier Racing Tire Corp. may suffer because of such sales. Not applicable where prohibited by law. Not following these warnings **CAN CAUSE SEVERE INJURY OR DEATH**. For more information read tire labels, follow manufacturer's warnings as molded in tire sidewalls and visit hoosiertire.com.

MOUNTING GUIDELINES

DRAG RACING TIRES, INCLUDING DOT DRAG TIRES:

(Includes catalog numbers beginning with 17, 18)

Hoosier drag tires can be mounted to rotate in either direction. Hoosier drag tires can also be flipped or reversed to provide even wear

INDEPENDENT DEALERS MUST ESTABLISH THEIR OWN PRICES.
FOR PRICING CONTACT YOUR NEAREST DISTRIBUTOR (SEE BACK COVER).
REFER TO NO WARRANTY POLICY AND WARNINGS.

WARNING

Verify Correct Wheel and Bead Flange: All tires are designed to be used on wheels that are manufactured to Tire and Rim Association (T&RA) specifications and tolerances. Some rims are non-standard or damaged and it is necessary to inspect the rim flange to assure proper fit. Consult your specific rim manufacturer to determine if your rim can be used in this application. Never attempt to install and inflate a tire of one bead diameter on a rim or wheel of a different bead diameter. Use of Hoosier Racing Tires on wheels with incorrect bead flanges or wheels that do not meet T&RA standards can cause the assembly to fail and burst with explosive force sufficient to cause serious personal injury or death.

WARNING

Special Tire Mounting Instructions: Tire changing should be done only by trained personnel using proper tools and procedures. Failure to follow safe mounting procedures could cause faulty positioning of the tire and cause the assembly to burst with explosive force sufficient to cause serious injury or death. Always inspect tire for kinked beads or other possible damage that may have occurred in shipping or storage. Clean rim and lubricate beads with rubber lubricant. Always lock rim on mounting machine or place in safety cage. Use a clip on chuck, an in-line valve with a pressure gauge or adjustable regulator and remote inflation/deflation device. Have enough air hose to stay out of the trajectory. Stand back.

WARNING

When seating beads never exceed maximum bead seating pressure as molded in tire sidewall. Never exceed manufacturer's maximum inflation pressure.

WARNING

NOT FOR HIGHWAY USE: All Hoosier Racing Tires including DOT labeled Hoosier Racing Tires are designed for racing purposes only on specified racing surfaces and are **not to be operated on public roadways**. DOT labeled Hoosier Racing Tires meet Department Of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

Exception – "PRO STREET".

WARNING

Service Life for Race Tires: Old tires can fail in use, causing loss of vehicle control and personal injury. Environmental conditions like temperature extremes, exposure to sunlight, electric arc, solvents, automotive fluids, and atmospheric pollutants accelerate the aging process. Hoosier Racing Tire strongly recommends that new (sticker) tires should be put in service within 2 years of date of purchase. Used (scuffed) tires have a shorter service life than new (sticker) tires. Poor storage and infrequent use accelerate the aging process.

WARNING

Chemical Treatment of Tires: Hoosier Racing Tires strictly forbids any chemical alteration of the tire carcass and/or tread compound, such as tire "soaking" or use of tread "softener." Hoosier Racing Tire strictly forbids the physical defacement (removal, altering or covering), of tire sidewall markings in any manner. Failure to comply with this warning could result in premature or catastrophic tire failure and may result in serious injury or death.